

DRYING

Vismec Hot Air Dryer



DESICCANT WHEEL DRYER



The HR DRYERS are used to remove surface moisture from non-hygroscopic thermoplastic materials.

TECHNICAL FEATURES

- ◆ Optimal performance in the removal of surface moisture
- ◆ Possibility to install directly on the injection molding machines or extruders
- ◆ Cooling stop to prevent thermal degradation of material in the hopper
- ◆ Drying hoppers in stainless steel
- ◆ Accurate control of the air temperature



DRYING

Vismec Hot Air Dryer



TECHNICAL FEATURES

MODEL	CODE	AIRFLOW	MAX TEMPERATURE	HEATING POWER	BLOWER POWER	TOTAL POWER	VOLTAGE	VOLUME	WEIGHT
50	01670	25 m ³ /h	140 °C	1 kW	0,07 kW	1,07 kW	230/50 V/Hz	50 dm ³	42 kg
100	01672	50 m ³ /h	140 °C	1,5 kW	0,2 kW	1,7 kW	400/50 V/Hz	100 dm ³	77 kg
150	01674	80 m ³ /h	140 °C	3,5 kW	0,5 kW	4 kW	400/50 V/Hz	150 dm ³	98 kg
200	01675	80 m ³ /h	140 °C	3,5 kW	0,5 kW	4 kW	400/50 V/Hz	200 dm ³	110 kg
300	01669	160 m ³ /h	140 °C	7 kW	1,6 kW	8,6 kW	400/50 V/Hz	300 dm ³	234 kg
400	01676	160 m ³ /h	140 °C	7 kW	1,6 kW	8,6 kW	400/50 V/Hz	400 dm ³	246 kg
600	01677	250 m ³ /h	140 °C	10,5 kW	2,4 kW	12,9 kW	400/50 V/Hz	600 dm ³	268 kg
800	01673	400 m ³ /h	140 °C	14 kW	3,9 kW	17,9 kW	400/50 V/Hz	800 dm ³	385 kg
2000	-	630 m ³ /h	140 °C	28 kW	5,5 kW	114,13 kW	400/50 V/Hz	2000 dm ³	-

COMBINATIONS

MODEL	50	100	150	200	300	400	600	800	2000
TROLLEY WITH WHEELS	NOT INCLUDED IN THE PRICE	NOT INCLUDED IN THE PRICE	NOT INCLUDED IN THE PRICE	NOT INCLUDED IN THE PRICE	NOT INCLUDED IN THE PRICE	NOT INCLUDED IN THE PRICE			
FLOOR STANDING FRAME							INCLUDED IN THE PRICE	INCLUDED IN THE PRICE	
FLOOR LEGS									INCLUDED IN THE PRICE